

DAILY DRIVEAWAY

COMPLETE VEHICLES READY
FOR IMMEDIATE DELIVERY

7.2T CURTAINSIDE



BUILT IN COLLABORATION WITH

Bodywork
Solutions

IVECO

Your partner for sustainable transport

DAILY DRIVEAWAY

TECHNICAL DESCRIPTION 7.2T CURTAINSIDE

CHASSIS		
DIMENSIONS	Wheelbase (mm)	5100
	GVW (kg)	7200
	GCW (kg)	10500 (inc. 3.3tn towing weight)
ENGINE	Model	70C18HA8
	Displacement (l)	2998
	Cylinders	4
	Power (hp)	180
	Torque (Nm)	430
	Emission	Euro VI HD (Heavy duty)
GEARBOX	Type	8speed HI-MATIC
SUSPENSION	Front	Quad-tor
	Rear	Multileaf rear springs
TYRES	Brand	Agilis low rolling tyres
	Dimension	225/75 R16
SERVICE INTERVALS		2 years /50,000km

STANDARD EQUIPMENT	
DAILY BUSINESS	
MANUAL AIR CON	
FOG LIGHTS	
ELECTRIC MIRRORS HTD/ADJ	
CRUISE CONTROL	
12V - 13 PIN PROVISION	
AIR CONDITIONING COMPRESSOR	
ADDITIONAL EQUIPMENT	
DVRS SEAT 3 D.O.F + LMBR SUPP	
LEATHER STEERING WHEEL	
FULL LED HEADLIGHTS	
DIGITAL BLUETOOTH RADIO (DAB) WITH INTEGRATED FUNCTIONS	
BODY BUILDER CONNECTOR	
LANE DEPARTURE WARNING + PROACTIVE LANE KEEPING ASSIST	
STORAGE CRADLE + USB	
ESP SYSTEM + CROSSWIND ASSIST	

BODY	
BODY TYPE	BWS Curtain
UNDERFRAME	Bolted galvanised Steel channel runners and cross bearers spaced at 406mm
BODY PANELS	Galvanised steel framed body c/w self supporting roof with full length GRP roof skin. GRP front bulkhead capped with vertical aluminium radius cappings
FLOOR	18mm Phenolic coated board fixed to every bearer
REAR CLOSURE	GRP White (RAL9010) Rear barn doors c/w externally mounted lever locks. Nearside door to open first
CURTAINS	Blue PVC curtains tensioned by black webbing straps with stainless steel locking buckles. Tensioned to front & rear. Black Pelmet
KICK STRIP	220mm Plywood
LOAD RESTRAINT	Galvanised steel V Groove side rails c/w 6 Pairs of Lashing Posts. Load restraint Track 18" inbound either side 6 pairs straps
INTERIOR LIGHTS	Internal PIR light
GENERAL	Thermoplastic rear wings, electrics to legal requirements
OPTION AVAILABLE: WITH TUCK-AWAY LIFT	BAR Cargo BC1000F2A IT Tuck-away lift 1200mm Platform

NOMINAL DIMENSIONS	BODY INTERNAL	BODY EXTERNAL	COMPLETE VEHICLE*	PAYLOAD	
LENGTH (mm)	6100	6230	8800	PAYLOAD (KG)**	3808
WIDTH (mm)	2360	2400	2400	PAYLOAD WITH TUCK-AWAY LIFT (KG)**	3385
HEIGHT (mm)	2325	2360	3305		

*without tuck-away lift

**payload subject to variance due to engineering tolerances